



## Safety gas solenoid valves

Product	Name	Description	Characteristics
	<b>EG25*M.* - EG30*M.* SERIES</b>	Gas solenoid valves	With 3/4 and 1 connections, operating pressure up to 500mbar and two flame levels power-driven adjustment.
	<b>RM6-RM12-RM15-RM25-RM30 SERIES</b>	Safety gas solenoid valves	open type, with manual opening, with 1/2, 3/4 and 1 connections, with a flow rate up to 23 m3/h, operating pressure up to 500mbar
	<b>GV/GVC15-GV/GVC25-GV/GVC30-GV/GVC40 Series</b>	Combined valve units	with 1/2, 3/4, 1 and 1 1/2 connections, operating pressure up to 500mbar
	<b>GC SERIES</b>	Solenoid valve unit	for small gas burners, operating pressure up to 100mbar
	<b>EG40 SERIES</b>	Gas solenoid valves	with 1 1/2 connection, with a flow rate up to 50 m3/h, operating pressure up to 200mbar
	<b>EG25-EG30 SERIES</b>	Gas solenoid valves	with 3/4 or 1 connections, with a flow rate up to 23 m3/h, operating pressure up to 500mbar
	<b>EG15 SERIES</b>	Gas solenoid valves	with 1/2 connection, with a flow rate up to 8,0 m3/h, operating pressure up to 500mbar



Product	Name	Description	Characteristics
	<b>EG12 SERIES</b>	Gas solenoid valves	with 1/2 connection, with a flow rate up to 7,5 m <sup>3</sup> /h, operating pressure up to 500mbar
	<b>EG6 SERIES</b>	Gas solenoid valves	with 1/4 or 3/8 connections, with a flow rate up to 3,9 m <sup>3</sup> /h, operating pressure up to 1bar
	<b>E8 SERIES</b>	Gas solenoid valves	with 1/8 or 1/4 connections, with a flow rate up to 0,8 m <sup>3</sup> /h, operating pressure up to 1bar
	<b>BE SERIES</b>	Coils for solenoid valves	Coils for gas and gas-oil solenoid valves; protection IP65; power supply voltage range from 12 to 240 Volt
	<b>E6-E11 SERIES</b>	Solenoid valves for light oil, naphtha, kerosene, water and steam	with 1/4, 3/8 or 1/2 connections, operating pressure up to 35bar
	<b>E7 SERIES</b>	Solenoid valves for light oil	with a flow rate up to 0,055 m <sup>3</sup> /h, operating pressure up to 20bar