



## DOMESTIC REGULATORS

These regulators are mainly used for household purpose and are suitable for single burner / two burner gas stoves as well as grill cum cooking ranges having total consumption of 500 Liters/Hr. of LPG.

R-0602 is Meter Regulator mainly developed for natural gas distribution through pipeline. In addition to pressure control system, it is having built in cut off valve, which ensures the working safety.

Type of Regulator	Max Inlet Pressure	Outlet Pressure Range	Gas Flow Rate	End Connection	Gas
 <p><b>R-0101</b></p>	0.5 - 17 Kg/Cm <sup>2</sup>	30 mbar (30 mm w.c.)	0.5 Nm <sup>3</sup> /hr	Inlet: Union Nut 21.8 x 14 TPI (LH)  Outlet: Nozzle to suit 1/4 " hose pipe	LPG
 <p><b>R-0302</b></p>	0.5 - 4 Kg/Cm <sup>2</sup>	30 mbar (30 mm w.c.)	0.5 Nm <sup>3</sup> /hr	1/2" BSPT (INT)	Natural Gas
 <p><b>R-0602</b></p>	35 - 100 mbar (350 - 1000 mm w.c.)	20 - 30 mbar (200 - 300 mm w.c.)	6 Nm <sup>3</sup> /hr	3/4" BSP(INT) or 3/4" BSPT(INT)	Natural Gas
 <p><b>R-1805</b></p>	0.5 - 17 Kg/Cm <sup>2</sup>	30 mbar (30 mm w.c.)	0.5 Nm <sup>3</sup> /hr	Inlet: To suit 22mm Dia S.C. valve  Outlet: Nozzle to suit 1/4" I.D. hose pipe	LPG