



## Preset Pressure Regulators

These regulators are having preset outlet pressure. However the outlet pressure can be slightly adjusted by rotating the spring adjusting screw. The Industrial Pressure Regulator R - 4109 is available with 4 different types of preset outlet pressures. These are suitable for canteen, restaurants & small industrial furnaces. R - 4110 I R - 4301 are low pressure medium flow pressure regulators, mainly used for industrial furnaces & other gas appliances. R -4202 regulator is mainly suitable for Natural Gas.

Type of Regulator	Max Inlet Pressure	Outlet Pressure Range	Gas Flow Rate	End Connection	Gas
	1 -17 Kg/cm <sup>2</sup>	(a) 0.03 Kg/cm <sup>2</sup>	8 Nm <sup>3</sup> / hr	<b>Inlet:</b> 21.8 x 14 TPI (L.H) Union Nut  <b>Outlet:</b> 1/2" BSP (INT)	LPG
		(a) 0.3 Kg/cm <sup>2</sup>	28 Nm <sup>3</sup> / hr		
		(a) 0.7 Kg/cm <sup>2</sup>	28 Nm <sup>3</sup> / hr		
		(a) 1 Kg/cm <sup>2</sup>	28 Nm <sup>3</sup> / hr		
	1 -17 Kg/cm <sup>2</sup>	0.03-0.3 Kg/cm <sup>2</sup>	40 Nm <sup>3</sup> / hr	<b>Inlet:</b> 1/2" BSP (INT)  <b>Outlet:</b> 3/4" BSP (INT)	LPG Natural Gas
	1 -17 Kg/cm <sup>2</sup>	0.03-0.3 Kg/cm <sup>2</sup>	40 Nm <sup>3</sup> / hr	1" BSP (INT)	LPG Natural Gas
	1 -17 Kg/cm <sup>2</sup>	0.03 Kg/cm <sup>2</sup>	10 Nm/hr <sup>3</sup>	1/2" BSP (INT) or 1/2" BSPT (INT)	Natural Gas
		0.5 Kg/cm <sup>2</sup>	30 Nm/hr <sup>3</sup>		