R.K. Instruments & Controls

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Brahma Solenoid Valve EG25*L.3*GMO

Brand: Brahma | Code/Part No.: 13932000 | Category: SOLENOID VALVES

Specifications

Type	**EG25*L.3*GMO**
Product Code	**13932000**
Connection	**DN20 · G 3/4" threaded**
Orifice Diameter	**Ø25 mm**
Class	**Class A, Group 2**
Max Pressure	**P max. 350 mbar**
Opening Type	**Slow opening, with flow adjuster**
Closing Time	**≤ 1 s**
Power Supply	**230V, 50-60Hz, 33W**
Protection	**IP54**
Solenoid Type	**BE8*GMO · Code 18813010**
Flow Rate	**15 m³/h gas (at ΔP 2.5 mbar)**
Operating Temperature	**-10°C to +60°C**
Standards	**EN 161; Gas Appliances Regulation (EU) 2016/426**
Compliance	**CE Marked, RoHS Compliant**



Description

The Brahma EG25*L.3*GMO is a Class A, Group 2 automatic gas solenoid valve with slow opening and an integrated flow adjuster, for burner, boiler and gas-train shut-off duty on G 3/4" (DN20) threaded connections with a Ø25 mm orifice. Rated to a 350 mbar max inlet pressure with IP54 enclosure protection, it runs on a 230V, 50-60Hz, 33W solenoid (type BE8*GMO, code 18813010), closes in ≤ 1 s and passes a nominal 15 m³/h at ΔP 2.5 mbar. Built to EN 161 and the EU Gas Appliances Regulation 2016/426, operating from -10°C to +60°C. Manufactured by Brahma, Italy, it is CE marked and RoHS compliant.

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.