R.K. Instruments & Controls

TECHNICAL DATASHEET

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Brahma Solenoid Valve EG30*L.2*GMO

Brand: Brahma | Code/Part No.: 13942500 | Category: SOLENOID VALVES

Specifications

Type	**EG30*L.2*GMO**
Product Code	**13942500**
Connection	**DN25 · G 1" threaded**
Orifice Diameter	**Ø30 mm**
Class	**Class A, Group 2**
Max Pressure	**P max. 200 mbar**
Opening Type	**Slow opening, with flow adjuster**
Power Supply	**230V, 50-60Hz, 33W**
Protection	**IP54**
Solenoid Type	**BE8*GMO · Code 18813017**
Flow Rate	**23 m³/h gas (at ΔP 2.5 mbar)**
Compliance	**CE Marked, RoHS Compliant**



Description

The Brahma EG30*L.2*GMO is a Class A, Group 2 automatic gas solenoid valve with slow opening and an integrated flow adjuster, for burner, boiler and gas-train shut-off duty on G 1" (DN25) threaded connections with a Ø30 mm orifice. Rated to a 200 mbar max inlet pressure with IP54 enclosure protection, it runs on a 230V, 50-60Hz, 33W solenoid (type BE8*GMO, code 18813017) and passes a nominal 23 m³/h at ΔP 2.5 mbar. Manufactured by Brahma, Italy, it is CE marked and RoHS compliant.

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.